



12246 Notenpultleuchte

» Double4 LED FlexLight «

1. Ausstattung & Abmessungen




2. Batterien/Akkus einsetzen oder wechseln



3. Lampe platzieren


3.a an PLATTEN



3.a.1 Klammer drücken und über die Notenpult- oder sonstige Platte (max.25mm) schieben...

3.a.2 ...bis die Platte am unteren Anschlag der Klammer innen anstößt


3.b an K&M-NOTENKÖPFEN



3.b.1 Klammer drücken und über die mittige platzierte Lyra des Notenkopfes schieben...

3.b.2 ...bis die Platte am oberen Anschlag innen anstößt

3.c auf TISCHEN und ABLAGEN




3.c.1 Lampenfuß auf eine ebene Unterlage stellen. Vier Auflagepunkte sorgen für einen wackelfreien Stand

3.c.2 Für die optimale Balance ggf. die Schwanenhäse mitsamt Leuchtkopf etwas korrigieren


4. Licht Ein- und Ausschalten

Beide Leuchtenköpfe sind unabhängig voneinander schaltbar

Durch mehrfaches Betätigen des Druckknopfes wird die Lichtstärke gesteuert:




Grundstellung = Licht AUS



Schaltzyklus beginnt erneut

5. Leuchtkopf einstellen



Durch die hochflexiblen Schwanenhäse können die Lichtkegel im Handumdrehen in wirklich jede gewünschte Position gebracht werden - und halten diese auch auf Dauer.

Produktdatenblatt

DELEGIERTE VERORDNUNG (EU) 2019/2015 DER KOMMISSION zur Energieverbrauchskennzeichnung von Lichtquellen

Name oder Handelsmarke des Lieferanten: KÖNIG & MEYER GmbH & Co.KG

Anschrift des Lieferanten: KÖNIG & MEYER GmbH & Co.KG , Kiesweg, 2, 97877 Wertheim, DE

Modellkennung: 12246

Art der Lichtquelle:

Verwendete Beleuchtungstechnologie:	LED	Ungebündelt oder gebündelt:	NDLS
Art des Sockels der Lichtquelle (oder andere elektrische Schnittstelle)	NO		
Netzspannung/Nicht direkt an die Netzspannung angeschlossen:	NMLS	Vernetzte Lichtquelle (CLS):	Ja
Farblich abstimmbare Lichtquelle:	Nein	Hülle:	-
Lichtquelle mit hoher Leuchtdichte:	Nein		
Blendschutzschild:	Nein	Dimmbar:	Ja


Produktparameter

Parameter	Wert	Parameter	Wert
Allgemeine Produktparameter:			
Energieverbrauch im Ein-Zustand (kWh/1000 h), auf die nächstliegende ganze Zahl gerundet	2	Energieeffizienzklasse	G
Nutzlichtstrom (ϕ_{use}) mit Angabe, ob sich der Wert auf den Lichtstrom in einer Kugel (360°), in einem breiten Kegel (120°) oder in einem schmalen Kegel (90°) bezieht	68 in schmaler Kegel (90°)	ähnliche Farbtemperatur, gerundet auf die nächstliegenden 100 K, oder Spanne der einstellbaren ähnlichen Farbtemperaturen, gerundet auf die nächstliegenden 100 K	6 000
Leistungsaufnahme im Ein-Zustand (P_{on}) in W	1,1	Leistungsaufnahme im Bereitschaftszustand (P_{sb}) in W, auf die zweite Dezimalstelle gerundet	0,00
Leistungsaufnahme im vernetzten Bereitschaftsbetrieb (P_{net})	0,00	Farbwiedergabeindex, auf die nächstliegende gan-	84


für CLS in W, auf die zweite Dezimalstelle gerundet			ze Zahl gerundet, oder Spanne der einstellbaren CRI-Werte	
äußere Abmessungen, ggf. ohne separates Betriebsgerät, Beleuchtungssteuerungsteile und Nicht-Beleuchtungsteile (Millimeter)	Höhe	340	Spektrale Strahlungsverteilung im Bereich 250 nm bis 800 nm bei Volllast	Siehe Bild auf letzter Seite
	Breite	70		
	Tiefe	20		
Angabe zu einer gleichwertigen Leistungsaufnahme ^(a)		-	Falls ja, gleichwertige Leistungsaufnahme (W)	-
			Farbwertanteile (x und y)	0,327 0,339
Parameter für LED- und OLED-Lichtquellen:				
Wert des R9-Farbwiedergabeindex		10	Lebensdauerfaktor	1,00
Lichtstromerhalt		0,97		

(a) „-“: nicht zutreffend;

(b) „-“: nicht zutreffend;



Model placed on the Union market from 01/11/2017



EPREL registration number: 1287075

<https://eprel.ec.europa.eu/qr/1287075>

Supplier: König & Meyer GmbH & Co.KG (Importer)

Website:

Customer care service:

Name: KÖNIG & MEYER GmbH & Co.KG

Website: <http://www.k-m.de>

Email: ck@k-m.de

Phone: +49 9342 806 106


Address:

Kiesweg, 2
97877 Wertheim
Deutschland

12246 Music stand light

» Double4 LED FlexLight«

1. Equipment & Dimensions




2. Batteries/rechargeable batteries insert or change

<p>2.a Battery case lid: Slide the lid with your thumb (approx. 6 mm) in the direction of the arrow.</p>	<p>2.b Unlock the lid and lift</p>	<p>2.c Insert three batteries (AAA-1.5V) i.e. rechargeable batteries (AAA-1.2V); (please pay attention to the poles +/-)</p>
<p>2.d Place the lid on the compartment</p>	<p>2.e Slide the lid with your thumb over the opening until both hooks click into place</p>	<p>2.f After the "click" ensure that the lid is securely in place</p>

3. Placement of the lamp


3.a to the PLATES



3.a.1 Press the clamp and slide the music desk or other plate (max. 25 mm)...

3.a.2 ...until the plate reaches the inside of the lower end of the clamp


3.b to K&M-NOTE HEADS



3.b.1 Press the clamp and slide the Lyra placed in the middle of the note head...

3.b.2 ...until the plate reaches the inside of the upper end of the clamp

3.c on TABLES and TRAYS




3.c.1 Place the lamp foot /base on a level surface. Four points of support ensure stability

3.c.2 To attain optimal balance adjust the goosenecks and the light head a bit

4. Turn Light On/Off

Both light heads can be turned on or off independently of each other

By repeated pressing of the press button the brightness is controlled:



Initial position = Light OFF


Press 1x = full brightness

Press 2x = less brightness

Press 3x = Light is turned OFF

The switching cycle begins again

5. Adjust the Light Head



The highly flexible goosenecks can be used to quickly place the light in the desired position - and it will stay there until it is adjusted again.

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: KÖNIG & MEYER GmbH & Co.KG

Supplier's address: KÖNIG & MEYER GmbH & Co.KG , Kiesweg, 2, 97877 Wertheim, DE

Model identifier: 12246

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	NO		
Mains or non-mains:	NMLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes


Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	2	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	68 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 000
On-mode power (P_{on}), expressed in W	1,1	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	0,00	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	84
Outer dimensions without separate control gear, lighting control	Height	340	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	70	
	Depth	20	
			See image in last page


parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,327 0,339
Parameters for LED and OLED light sources:			
R9 colour rendering index value	10	Survival factor	1,00
the lumen maintenance factor	0,97		

(a) : not applicable;

(b) : not applicable;



Model placed on the Union market from 01/11/2017



EPREL registration number: 1287075

<https://eprel.ec.europa.eu/qr/1287075>

Supplier: König & Meyer GmbH & Co.KG (Importer)

Website:

Customer care service:

Name: KÖNIG & MEYER GmbH & Co.KG

Website: <http://www.k-m.de>

Email: ck@k-m.de

Phone: +49 9342 806 106

Address:

Kiesweg, 2
97877 Wertheim
Germany